## NSN 5305-00-625-4321

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-625-4321 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.265 inches **Fastener Length:** 0.820 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.560 inches **Head Height:** 0.300 inches **First Diameter From Head:** 0.300 inches **Second Diameter From Head:** Between 0.139 inches and 0.149 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.080 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.380 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Special Features:** Cone point 90 degrees of angle Material: Steel comp 303 or steel comp 303se **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unf

N/a

Shelf Life:

## NSN 5305-00-625-4321

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0