NSN 5305-00-626-2673

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-626-2673 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.141 inches and 0.171 inches **Fastener Length:** Between 0.985 inches and 1.015 inches **Head Style:** Pan **Head Diameter:** Between 0.240 inches and 0.260 inches **Head Height:** 0.103 inches **First Diameter From Head:** 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.814 inches and 0.874 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Flat point Material: Steel comp 416 **Material Specification:** Qq-s-764, cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-626-2673

Externally Relieved Body Screw - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.