Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-626-2673

Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
Between 0.141 inches and 0.171 inches
Fastener Length:
Between 0.985 inches and 1.015 inches
Head Style:
Pan
Head Diameter:
Between 0.240 inches and 0.260 inches
Head Height:
0.103 inches
First Diameter From Head:
0.093 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.814 inches and 0.874 inches
Internal Drive Style:
Slot
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Special Features:
Flat point
Material:
Steel comp 416
Material Specification:
Qq-s-764, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.