Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-630-3557

Thread C	ilass:
2a	
Thread D	Direction:
Right-han	nd
Thread L	ength:
0.125 incl	hes
Fastener	Length:
0.250 incl	hes
Head Sty	le:
Pan	
Head Dia	meter:
Between	0.205 inches and 0.219 inches
Head Hei	ight:
Between	0.070 inches and 0.080 inches
First Dia	meter From Head:
Between	0.073 inches and 0.077 inches
Distance	From Largest Bearing Surface Of Head To End Of First Diameter:
0.125 incl	hes
Internal [Drive Style:
Cross rec	ess type 1
Thread D	viameter:
0.112 incl	hes
Thready	Qty Per Inch (tpi):
40	
Externall	y Relieved Body Diameter Quantity:
1	
Material:	
Steel com	np 410 or steel comp 416
Material	Specification:
Qq-s-763	federal specification 1st material response or astm a582 assn standard 2nd material response
Surface T	Treatment:
Passivate	
Surface 1	Freatment Specification:
Qq-p-35 f	ederal specification single treatment response
Thread S	eries Designator:
Unc	
Shelf Life	9:
N/a	
Unit Of N	leasure:
Demilitar	ization:
No	

NSN 5305-00-630-3557

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

