Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-630-6463

| Thread Clas | ss: |
|----------------------------|---|
| 2a | |
| ∠u Thread Dire | action |
| Right-hand | |
| Thread Len | ath. |
| 0.219 inches | |
| Fastener Le | - |
| 0.687 inches | |
| Head Style: | |
| Fillister | • |
| Head Diam | otor |
| | 205 inches and 0.219 inches |
| | |
| Head Heigh | n: 070 inches and 0.080 inches |
| | eter From Head: |
| 0.070 inches | |
| | - |
| 0.312 inches | rom Largest Bearing Surface Of Head To End Of First Diameter: |
| | |
| Internal Dri | |
| Cross reces Thread Dia | |
| | |
| 0.112 inches | |
| 40 | y Per Inch (tpi): |
| - | Relieved Body Diameter Quantity: |
| Externally r | Neneveu Douy Diameter Wuditility. |
| Material: | |
| Steel comp | 416 |
| - | ecification: |
| - | deral specification single material response |
| Qq-s-763 le Surface Tre | |
| Passivate | |
| | ies Designator: |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Mea | asure: |
| | |
| Demilitariza | ation |
| No | |
| Fiig: | |
| | |