## NSN 5305-00-631-1287

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-631-1287 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** Between 2.046 inches and 2.078 inches **Head Style:** Fillister **Head Diameter:** Between 0.389 inches and 0.414 inches **Head Height:** 0.155 inches **First Diameter From Head:** Between 0.245 inches and 0.250 inches **Second Diameter From Head:** 0.188 inches **Third Diameter From Head:** 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.468 inches and 0.478 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.582 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.063 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

171, finish no. 5.4.1 military standard single treatment response

## NSN 5305-00-631-1287

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0