Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-631-1287

Thread Class:	
2a	
Za Thread Direction:	
Right-hand	
Thread Length:	
1.000 inches	
Fastener Length:	
Between 2.046 inches and 2.078 inches	
Head Style:	
Fillister	
Head Diameter:	
Between 0.389 inches and 0.414 inches	
Head Height:	
0.155 inches	
First Diameter From Head:	
Between 0.245 inches and 0.250 inches	
Second Diameter From Head:	
0.188 inches	
Third Diameter From Head:	
0.250 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
Between 0.468 inches and 0.478 inches	
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:	
0.582 inches	
Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.063 inches	
Internal Drive Style:	
Slot	
Thread Diameter:	
0.250 inches	
Thready Qty Per Inch (tpi):	
20	
Externally Relieved Body Diameter Quantity:	
3	
Material:	
Steel comp 303	
Material Specification:	
Astm a582 assn standard single material response	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
171, finish no. 5.4.1 military standard single treatment response	
Transmitter of the minimum standard single treatment response	

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0