## NSN 5305-00-637-0304

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-637-0304 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.657 inches **Fastener Length:** 2.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.863 inches and 0.875 inches **Head Height:** Between 0.618 inches and 0.625 inches **Shoulder Diameter:** 0.6254 inches first shoulder and 0.6259 inches first shoulder **Shoulder Length:** 1.156 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 13 **Shoulder Shape:** Round first shoulder **Special Features:** Relieved under head 0.093 in. W 0.593 in. Dia. Of relief and relieved at base of thd. 0.093 in. W 0.390 in. Dia. Of relief Steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144 **Surface Treatment:** Phosphate **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5305-00-637-0304** Shoulder Screw - Page 2 of 2



Fiig:

A003b0