## NSN 5305-00-637-0484

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-637-0484 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.344 inches and 0.406 inches **Fastener Length:** Between 0.803 inches and 0.823 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.469 inches and 0.531 inches **Head Height:** Between 0.344 inches and 0.406 inches **First Diameter From Head:** Between 0.175 inches and 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.397 inches and 0.478 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 **Material Specification:** Mil-s-7720 military specification 1st material response or qq-s-763 federal specification 2nd material response or astm a582 assn standard 2nd material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A003b0

Mil-s-7720 spec.

Mil-std (military Standard):