

View Online at <https://aerobasegroup.com/nsn/5305-00-637-6811>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.640 inches

**Fastener Length:**

Between 1.687 inches and 1.734 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.752 inches and 0.762 inches

**Shank Unthreaded Hole Diameter:**

1.500 inches first hole

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 0.219 inches and 0.221 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Minimum Yield Strength:**

160000 pounds per square inch

**Countersink Angle:**

100.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.106 inches first hole

**Material:**

Steel

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas336-15 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0