Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-637-7200

3a Thread Direction:
Thread Direction:
Right-hand
Thread Length:
1.312 inches
Fastener Length:
3.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.429 inches and 0.438 inches
Head Height:
Between 0.306 inches and 0.312 inches
Hole Diameter:
0.047 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
0.219 inches
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Product Name:
Navy special project
Material:
Steel
Material Specification:
66 federal standard single material response

# NSN 5305-00-637-7200

Socket Head Cap Screw - Page 2 of 2



Surface Treatment:

Zinc

### Surface Treatment Specification:

Qq-z-325, type 2, cl 3 federal specification single treatment response

#### Thread Series Designator:

Unf

# **Specification Or Standard:**

1 type

## Departure From Cited Designator:

As modified by head hole configuration

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A003b0