## NSN 5305-00-637-8803

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-637-8803 **Thread Direction:** Right-hand Thread Length: Between 0.740 inches and 0.820 inches Fastener Length: Between 1.300 inches and 1.320 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.865 inches and 0.885 inches **Head Height:** Between 0.300 inches and 0.320 inches **Shoulder Diameter:** 0.499 inches first shoulder and 0.501 inches first shoulder **Shoulder Length:** 0.193 inches first shoulder and 0.195 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches **Nonstandard Thread Pitch Diameter:** +0.2797/+0.2824 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Uns Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-00-637-8803

Shoulder Screw - Page 2 of 2



Fiig:

A003b0