NSN 5305-00-637-8803

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-637-8803

Thread Direction:
Right-hand
Thread Length:
Between 0.740 inches and 0.820 inches
Fastener Length:
Between 1.300 inches and 1.320 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.865 inches and 0.885 inches
Head Height:
Between 0.300 inches and 0.320 inches
Shoulder Diameter:
0.499 inches first shoulder and 0.501 inches first shoulder
Shoulder Length:
0.193 inches first shoulder and 0.195 inches first shoulder
Internal Drive Style:
Slot
Thread Diameter:
0.312 inches
Nonstandard Thread Pitch Diameter:
+0.2797/+0.2824 inches
Thready Qty Per Inch (tpi):
24
Hardness Rating:
30.0 rockwell c and 38.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel
Surface Treatment:
Nickel and cadmium
Surface Treatment Specification:
Ams 2416 assn standard all treatment responses
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
_
Demilitarization:
No

NSN 5305-00-637-8803

Shoulder Screw - Page 2 of 2

Fiig: A003b0

