

View Online at <https://aerobasegroup.com/nsn/5305-00-637-9277>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.469 inches

Fastener Length:

0.906 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.293 inches and 0.306 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Countersink Angle:

100.0 degrees

Screw Material:

Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4037

Screw Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6758 military specification 4th material response or mil-s-8695 military specification 5th material response

Screw Surface Treatment:

Cadmium

Special Features:

Hd hieght 0.047

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6049 spec.