## NSN 5305-00-637-9277



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-637-9277 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** 0.906 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.293 inches and 0.306 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4037 **Screw Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6758 military specification 4th material response or mil-s-8695 military specification 5th material response **Screw Surface Treatment:** Cadmium **Special Features:** Hd hieght 0.047 **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:** 

## NSN 5305-00-637-9277

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.