## NSN 5305-00-638-0635



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-638-0635 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.439 inches and 0.510 inches **Fastener Length:** Between 0.490 inches and 0.510 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.389 inches and 0.414 inches

**Head Height:** 

Between 0.256 inches and 0.276 inches

**Hole Diameter:** 0.070 inches

**Internal Drive Style:** 

**Thread Diameter:** 

0.250 inches

**Hole Quantity:** 

2

Slot

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

**Screw Material:** 

Steel comp 8740

**Screw Material Specification:** 

Ams 6322 assn standard single material response

**Screw Surface Treatment:** 

Cadmium

**Screw Surface Treatment Specification:** 

Ams 2400 assn standard single treatment response

**Head Hole Configuration Style:** 

Round

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

## NSN 5305-00-638-0635

Machine Screw - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A500d0