Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-638-1327

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.250 inches
Fastener Length:
1.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Hole Diameter:
0.067 inches
Internal Drive Style:
Hexagon Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.312 inches and 0.316 inches
Hole Quantity:
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
16 Min Tanaila Stannath (nail)
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 43.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium and chromate

NSN 5305-00-638-1327

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-416 type 2 class 3 federal specification all treatment responses

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0