

NSN 5305-00-638-1419 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-638-1419 **Thread Class:** За

Thread Direction: Right-hand Thread Length: Between 0.830 inches and 1.080 inches **Fastener Length:**

Between 1.210 inches and 1.250 inches **Head Style:**

Flat chamfer **Head Diameter:**

Between 0.303 inches and 0.312 inches

Head Height:

Between 0.185 inches and 0.195 inches

Hole Diameter:

0.044 inches

Hexagon

Internal Drive Style:

Thread Diameter:

0.190 inches

Width Across Flats:

Between 0.156 inches and 0.159 inches

Hole Quantity:

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Hole Configuration Style:

Round longitudinal hole

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

NSN 5305-00-638-1419

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A003b0