NSN 5305-00-638-1583



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-638-1583 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.203 inches **Fastener Length:** 0.438 inches **Head Style:** Flat chamfer **Head Diameter:** 0.281 inches **Head Height:** 0.062 inches **First Diameter From Head:** 0.219 inches **Second Diameter From Head:** 0.141 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.188 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.234 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1524 or steel comp 1025 or steel comp 1527 or steel comp 1030 or steel comp 1035 or steel comp 1109 or steel comp 1117 or steel comp 1118 or steel comp 1120 **Material Specification:** Gastm a576 military specification all material responses **Surface Treatment:** Chromate zinc **Thread Series Designator:** Unc

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-638-1583

Externally Relieved Body Screw - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

spec.