## NSN 5305-00-638-1614

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-638-1614 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** 0.625 inches **Head Style:** Fillister **Head Diameter:** Between 0.248 inches and 0.270 inches **Head Height:** Between 0.102 inches and 0.113 inches **First Diameter From Head:** 0.109 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.281 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1010 **Material Specification:** Qq-s-630 federal specification single material response or qq-s-631 federal specification single material response or qq-s-634 federal specification single material response **Surface Treatment:** Cadmium and chromate or paint **Surface Treatment Specification:** Qq-p-416, type 2 cl b federal specification 1st treatment response or qq-p-416, type 2 cl b federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-00-638-1614

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0