NSN 5305-00-638-1648

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-638-1648 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.422 inches **Fastener Length:** 0.722 inches **Head Style:** Flat chamfer **Head Diameter:** 0.625 inches **Head Height:** Between 0.143 inches and 0.153 inches **First Diameter From Head:** Between 0.410 inches and 0.420 inches **Second Diameter From Head:** Between 0.435 inches and 0.436 inches **Third Diameter From Head:** 0.260 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.047 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.253 inches and 0.255 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.300 inches and 0.302 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment:** Passivate and oxide **Thread Series Designator:**

Unf

NSN 5305-00-638-1648

Externally Relieved Body Screw - Page 2 of 2



Sh	elf	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0