Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-638-1649

Thread Class: 2a Thread Direction: Right-hand Right-hand Direct Length: 0.344 incles Fastener Length: 0.354 incles Fastener Length: 0.354 incles Fastener Length: 0.355 incles Head Direction: 0.375 incles Head Fagith: 0.350 incles Castoner From Head: 0.363 incles Biotener: 0.363 incles Scood Diameter From Head: 0.404 incles Scood Diameter From Head: 0.404 incles Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.404 incles Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.404 incles Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.404 incles Herenal Drive Style: Cisce as type 1 Hored Diameter: 0.404 incles Herenal Drive Style: 1 Herenal Drive Style:	New Online at https://aerobasegroup.com/nsi//3503-00-050-1049	
Thread Direction:Right-handThread Length:0.344 inchesFastener Length:0.398 inchesHead Style:Knurled no. 1Head Diameter:0.375 inchesHead Height:0.375 inchesHead Height0.368 inchesFirst Diameter From Head:0.164 inchesStatener From Head:0.164 inchesBestone From Largest Bearing Surface Of Head To End Of First Diameter:0.494 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesInternal Drive Style:Cross recess type 1Thread Diameter:11Hole Type:DialdInternal Drive Style:11Hole Type:DialdDiadeFirst Diameter:11Hole Type:DialdConfiguration Style:RicundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screewHouris:1Houris:1111122222	Thread Class:	
Righ-hand	2a	
Thread Length:0.344 inchesFastener Length:0.938 inchesHead Skyle:Kourled no. 1Head Diameter:0.375 inchesHead Height:0.375 inchesHead Height:0.353 inchesHold Diameter:0.063 inchesFirst Diameter From Head:0.164 inchesSecond Diameter From Head:0.109 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.409 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.409 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.409 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.409 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.404 inchesHead Diameter:1Head Diameter:1Head Diameter:1Head Diameter:1Head Diameter: <t< td=""><td>Thread Direction:</td><td></td></t<>	Thread Direction:	
0.444 inchesFastener Length:0.938 inchesHead Siyle:Knurled no. 1Head Diameter:0.375 inchesHead Height:0.260 inchesHole Diameter From0.063 inchesFirst Diameter From Head:0.164 inchesSecond Diameter From Head:0.109 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.409 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.409 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.409 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.409 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.409 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.409 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.409 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesHole Contiguration Style:NiledIntready Qty Per Inch (tpl):32KoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	Right-hand	
Fastener Length: 0.938 inches Head Style: Knurde no. 1 Head Diameter: 0.375 inches Head Height: 0.250 inches Hold Diameter: 0.633 inches First Diameter From Head: 0.104 inches Second Diameter From Head: 0.109 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.404 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.404 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.404 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.404 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 Hole Quantity: 1 Hole Configuration Style: Round Hole Configuration Style: Round Hole Configuration Style: Round Extensity Relieved Body Diamet	Thread Length:	
0.938 inches Head Style: Knurled no. 1 Head Diameter: 0.375 inches Head Height: 0.250 inches Hole Diameter: 0.063 inches First Diameter From Head: 0.164 inches Second Diameter From Head: 0.109 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.400 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.400 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.400 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.400 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.401 inches Hear Diameter: 0.402 inches Hole Zumatity: 1 Hole Zumatity: 1 Hole Zumatity: 2 Head Configuration Style: Raud Externally Relieved Body Diameter Quantity: 2 Special Features: <tr< td=""><td>0.344 inches</td><td></td></tr<>	0.344 inches	
Head Style: Knuted no. 1 Head Diameter: 0.375 inches Head Height: 0.250 inches Head Height: 0.263 inches Hole Diameter: 0.063 inches First Diameter From Head: 0.164 inches Becond Diameter From Head: 0.109 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.400 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.594 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Hole Type: Dified Hole Type: Dified Hole Configuration Style: Round Lec Configuration Style: Round Rue Hole Type: Dified Hole Configuration Style: Round Special Features: Also Gouge to point at thread end of screw Meterial:	Fastener Length:	
Kurded no. 1 Head Diameter: 0.375 inches Head Height: 0.250 inches Hole Diameter: 0.063 inches First Diameter From Head: 0.164 inches Second Diameter From Head: 0.109 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.40 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.49 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.40 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.49 inches Interad Diameter: 0.164 inches Hole Quantity: 1 Hole Type: Diriked Hole Type: Diriked Hole Configuration Style: Round Round Round Sternally Relieved Body Diameter Quantity: 2 Special Features: 4.0 diagree to point at thread end of screw	0.938 inches	
Head Diameter:0.375 inchesHead Height:0.250 inchesHole Diameter:0.063 inchesFirst Diameter From Head:0.164 inchesSecond Diameter From Head:0.109 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.400 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesInternal Drive Style:Cross arcess type 1Thread Diameter:0.164 inchesHole Quantity:11Hole Type:DrilledThready Oty Per Inch (tpi):32RoundExternally Relieved Body Diameter Quantity:2Special Features:4.0.0 digree to point at thread end of screwMaterial:	Head Style:	
0.375 inchesHead Height:0.250 inchesHole Diameter:0.063 inchesFirst Diameter From Head:0.164 inchesSecond Diameter From Head:0.109 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.400 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesHole Quantity:11Strace Origination Style:Cross recess type 1Thread Olameter:0.154 inchesHole Cuantity:11Hole Type:DiriledStrace Origination Style:RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	Knurled no. 1	
Head Height:0.250 inchesHole Diameter:0.063 inchesFirst Diameter From Head:0.164 inchesSecond Diameter From Head:0.109 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.040 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.040 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesHole Quantity:1PildeDirledIntread Dirley Filnen (tpi):32RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	Head Diameter:	
0.250 inches Hole Diameter: 0.063 inches First Diameter From Head: 0.164 inches Second Diameter From Head: 0.109 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.400 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.400 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.401 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.402 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 Hole Type: Diriked Diriked Hole Configuration Style: Round Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screw	0.375 inches	
Hole Diameter: 0.063 inches First Diameter From Head: 0.164 inches Second Diameter From Head: 0.109 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.040 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.040 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.594 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 Hole Type: Diriked Thready Quy Per Inch (tpi): 32 Hole Configuration Style: Round Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screw	Head Height:	
0.063 inchesFirst Diameter From Head:0.164 inchesSecond Diameter From Head:0.109 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.040 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesHole Quantity:11Hole Type:DrilledThready Qty Per Inch (tpi):32Hole Configuration Style:RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	0.250 inches	
First Diameter From Head: 0.164 inches Second Diameter From Head: 0.109 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.040 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.594 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 Hole Type: Drilled Thready Dyper Inch (tpi): 32 Hole Configuration Style: Round Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screey	Hole Diameter:	
0.164 inchesSecond Diameter From Head:0.109 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.040 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesHole Quantity:1Hole Type:DrilledThready Qty Per Inch (tp):32Hole Configuration Style:RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	0.063 inches	
Second Diameter From Head:0.109 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.040 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesHole Quantity:11Hole Type:DrilledDready Oty Per Inch (tpi):32RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMeterial:	First Diameter From Head:	
0.109 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.040 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesHole Quantity:11Hole Type:DrilledBriendy Otyper Inch (tpi):32Hole Configuration Style:RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	0.164 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:0.040 inchesDistance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesHole Quantity:11Hole Type:DrilledDrived Qty Per Inch (tpi):32RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	Second Diameter From Head:	
0.040 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.594 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Round Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screw	0.109 inches	
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:0.594 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesHole Quantity:1Hole Type:DrilledDrineady Qty Per Inch (tpi):32Hole Configuration Style:RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
0.594 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Round Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screw Material:	0.040 inches	
Internal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesHole Quantity:11Hole Type:DrilledThready Qty Per Inch (tpi):32Hole Configuration Style:RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	Distance From Largest Bearing Surface Of Head To End Of Second Diameter:	
Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 1 Hole Type: Drilled Drilled Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Round Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screw	0.594 inches	
Thread Diameter:0.164 inchesHole Quantity:11Hole Type:DrilledThready Qty Per Inch (tpi):32Hole Configuration Style:RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	Internal Drive Style:	
0.164 inches Hole Quantity: 1 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Round Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screw Material:	Cross recess type 1	
Hole Quantity:11Hole Type:DrilledThready Qty Per Inch (tpi):32Hole Configuration Style:RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	Thread Diameter:	
1Hole Type:DrilledThready Qty Per Inch (tpi):32Hole Configuration Style:RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	0.164 inches	
Hole Type:DrilledThready Qty Per Inch (tpi):32Hole Configuration Style:RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:	Hole Quantity:	
Drilled Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Round Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screw Material:		
Thready Qty Per Inch (tpi):3232Hole Configuration Style:RoundExternally Relieved Body Diameter Quantity:2Special Features:45.0 degree to point at thread end of screwMaterial:		
32 Hole Configuration Style: Round Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screw		
Hole Configuration Style: Round Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screw Material:		
Round Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screw Material:		
Externally Relieved Body Diameter Quantity: 2 Special Features: 45.0 degree to point at thread end of screw Material:		
2 Special Features: 45.0 degree to point at thread end of screw Material:		
Special Features: 45.0 degree to point at thread end of screw Material:		
45.0 degree to point at thread end of screw Material:		
Material:		
Steel comp 303 or steel comp 303se		
	Steel comp 303 or steel comp 303se	

Externally Relieved Body Screw - Page 2 of 2



Material Specification:

Astm a582 assn standard all material responses

Surface Treatment:

Passivate

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0