## NSN 5305-00-638-2845

Externally Relieved Body Screw - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5305-00-638-2845           |
|---|
| Thread Class:   |
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.063 inches and 0.078 inches                                   |
| Fastener Length:  |
| Between 0.088 inches and 0.093 inches                                   |
| Head Style:   |
| Fillister   |
| Head Diameter:  |
| Between 0.234 inches and 0.266 inches                                   |
| Head Height:  |
| Between 0.020 inches and 0.025 inches                                   |
| First Diameter From Head:   |
| Between 0.066 inches and 0.076 inches                                   |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| Between 0.015 inches and 0.025 inches                                   |
| Internal Drive Style:   |
| Cross recess type 1   |
| Thread Diameter:  |
| 0.099 inches  |
| Thready Qty Per Inch (tpi):   |
| 48  |
| Externally Relieved Body Diameter Quantity:                             |
| 1   |
| Material:   |
| Steel comp 303  |
| Material Specification:   |
| Qq-s-763 federal specification single material response                 |
| Surface Treatment:  |
| Passivate   |
| Thread Series Designator:   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiia:   |

A003b0