## NSN 5305-00-638-5031

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-638-5031 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** 2.200 inches **Head Style:** Fillister **Head Diameter:** Between 0.208 inches and 0.226 inches **Head Height:** Between 0.085 inches and 0.093 inches **First Diameter From Head:** Between 0.113 inches and 0.123 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.200 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 20.0 rockwell c and 24.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 8740 or steel comp 4130 or steel comp 4037 **Surface Treatment:** Cadmium and chromate and chromium **Surface Treatment Specification:** Qq-p-416 type 2, class 2 federal specification 1st treatment response and mil-p-6871 type 2, class a military specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-00-638-5031

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-p-6871 spec.