NSN 5305-00-638-5039

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-638-5039 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.070 inches **Fastener Length:** 0.180 inches **Head Style:** Flat countersunk **Head Diameter:** 0.120 inches First Diameter From Head: 0.078 inches **Second Diameter From Head:** 0.050 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.090 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.110 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.073 inches Thready Qty Per Inch (tpi): 72 Hardness Rating: 65.0 rockwell b and 85.0 rockwell b Minimum Yield Strength: 28000 pounds per square inch **Countersink Angle:** 82.0 degrees **Externally Relieved Body Diameter Quantity:** 2 Material: Copper alloy 360 **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-638-5039

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0