Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-638-5039

Thre	ead Class:
2a	
Thre	ead Direction:
Rigł	nt-hand
Thre	ead Length:
0.07	0 inches
Fas	tener Length:
0.18	0 inches
Hea	d Style:
Flat	countersunk
Hea	d Diameter:
0.12	10 inches
Firs	t Diameter From Head:
0.07	8 inches
Sec	ond Diameter From Head:
0.05	0 inches
Dist	ance From Largest Bearing Surface Of Head To End Of First Diameter:
0.09	0 inches
Dist	ance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.11	0 inches
Inte	rnal Drive Style:
Slot	
Thre	ead Diameter:
0.07	3 inches
Thre	eady Qty Per Inch (tpi):
72	
Har	dness Rating:
65.0	rockwell b and 85.0 rockwell b
Min	imum Yield Strength:
280	00 pounds per square inch
Cou	intersink Angle:
82.0	degrees
Exte	ernally Relieved Body Diameter Quantity:
2	
Mat	erial:
Сор	per alloy 360
Thre	ead Series Designator:
Unf	
She	If Life:
N/a	
Unit	Of Measure:

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0