NSN 5305-00-638-7878

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-638-7878 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.292 inches and 0.342 inches **Fastener Length:** Between 1.302 inches and 1.322 inches **Head Style: Button Head Diameter:** Between 0.406 inches and 0.446 inches **Head Height:** Between 0.103 inches and 0.113 inches **First Diameter From Head:** Between 0.184 inches and 0.190 inches **Second Diameter From Head:** Between 0.136 inches and 0.151 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.230 inches and 0.260 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.980 inches and 1.010 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 1018 **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-00-638-7878

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0