## NSN 5305-00-638-9992

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-638-9992



**Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.678 inches and 0.740 inches Fastener Length: Between 0.740 inches and 0.760 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.160 inches and 0.171 inches Hole Diameter: 0.046 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity:** 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b **Screw Material:** Steel **Screw Material Specification:** Ams 5061 assn standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Ams 2400 assn standard single treatment response Head Hole Configuration Style: Round **Thread Series Designator:** 

Unc

Shelf Life:

N/a

## NSN 5305-00-638-9992

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

