NSN 5305-00-639-4516

Machine Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-639-4516

| Thread Class: | |
|-------------------|--|
| 3a | |
| Thread Directio | n: |
| Right-hand | |
| Thread Length: | |
| 0.406 inches | |
| Fastener Lengt | h: |
| Between 1.703 in | nches and 1.733 inches |
| Head Style: | |
| Flat countersunk | |
| Head Diameter: | |
| 0.332 inches | |
| Internal Drive S | tyle: |
| Cross recess typ | ne 1 |
| Thread Diamete | er: |
| 0.190 inches | |
| Thready Qty Pe | r Inch (tpi): |
| 32 | |
| Countersink An | gle: |
| Between 99.0 de | grees and 101.0 degrees |
| Screw Material: | |
| Nickel alloy k-50 | 0 or copper alloy 172 |
| Screw Material | Specification: |
| Qq-n-286 cl a fe | deral specification 1st material response or qq-c-530 cond a federal specification 2nd material response |
| Screw Surface | Treatment: |
| Cadmium | |
| Screw Surface | Treatment Specification: |
| Qq-p-416, type | 1, cl 3 federal specification single treatment response |
| Thread Series D | Designator: |
| Unf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure | e: |
| | |
| Demilitarization | : |
| No | |
| Fiig: | |
| A500d0 | |