## NSN 5305-00-639-4534

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-639-4534

The	ad Class:
3a <b>T</b> h ra	ad Disastion
	ead Direction:
-	t-hand
	ead Length:
	2 inches
	ener Length:
	veen 1.235 inches and 1.297 inches
	d Style:
	countersunk
	d Diameter:
	veen 0.497 inches and 0.507 inches
	nk Unthreaded Hole Diameter:
	6 inches first hole
	nal Drive Style:
Hexa	agon
Thre	ad Diameter:
0.25	0 inches
Widt	th Across Flats:
Betw	veen 0.156 inches and 0.157 inches
Thre	eady Qty Per Inch (tpi):
28	
Min.	Tensile Strength (psi):
1600	000 pounds per square inch
Cou	ntersink Angle:
100.	0 degrees
Dist	ance From Head Largest Bearing Surface To Shank Hole Center:
1.11	6 inches first hole and 1.136 inches first hole
Mate	erial:
Stee	1
Surf	ace Treatment:
Cad	mium head
Thre	ad Series Designator:
Unf	
She	if Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	
Fiig:	
A003	3b0