## NSN 5305-00-639-4665

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-639-4665



### **Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.965 inches and 1.125 inches Fastener Length: Between 1.065 inches and 1.125 inches **Head Style:** Fillister **Head Diameter:** Between 0.389 inches and 0.414 inches **Head Height:** Between 0.161 inches and 0.170 inches Hole Diameter: 0.062 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Hole Quantity:** 1 Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:**

Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se

#### Screw Material Specification:

66 federal standard all material responses

#### Screw Surface Treatment:

Passivate

#### Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### Head Hole Configuration Style:

Round

#### **Thread Series Designator:**

Unc

#### **Specification Or Standard:**

1 type and 5s style

#### Shelf Life:

N/a

# NSN 5305-00-639-4665

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

