NSN 5305-00-639-5308

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-639-5308 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.174 inches and 0.204 inches **Fastener Length:** Between 0.928 inches and 0.948 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.160 inches and 0.170 inches **Head Height:** Between 0.058 inches and 0.078 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.125 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 150000 pounds per square inch **Hardness Rating:** Between 35.0 rockwell c and 38.0 rockwell c **Screw Material:** Steel comp 4130 **Screw Material Specification:** Mil-s-6758 military specification single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1 federal specification single treatment response **Special Features:** Cadmium plating 0.00015 in. Maximum thk **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-639-5308

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6758 spec.