NSN 5305-00-639-6514

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-639-6514 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.408 inches **Fastener Length:** 0.470 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Hole Diameter:** 0.047 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.158 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 123000 pounds per square inch Hardness Rating: 26.0 rockwell c and 34.0 rockwell c **Hole Configuration Style:** Round longitudinal hole **Product Name:** Navy special project Material: Steel comp 416se or steel comp 303 or steel comp 303 plus x **Surface Treatment: Passivate Thread Series Designator:**

Unf

NSN 5305-00-639-6514

Socket Head Cap Screw - Page 2 of 2



| _ | | | | | |
|----|----|----|-----|------|--|
| C. | ~~ | 14 | I i | ife: | |
| J. | 16 | | | HE. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0