Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-639-7334

a         Thread Direction:         Right-hand         Thread Length:         0.875 inches         Fastener Length:         0.875 inches         Head Style:         O.150 inches         Hole Diameter:         0.440 inches         Hole Quantity:         6         Hole Quantity:         6         Hole Style:         Drilled         Thread String:         3.0 rockwell c and 35.0 rockwell c         Hole Configuration Style:         Hexagon longitudinal hole         Material         Steel comp 8640         Material Specification: <th>3a         Thread Direction:         Right-hand         Thread Length:         0.875 inches         Fastener Length:         0.875 inches         Head Style:         Nead Style:         O.150 inches         Width Between Flats:         0.440 inches         Thread Diameter:         0.062 inches         Hole Quantity:         0.62         Thread Diameter:         0.250 inches         Hole Quantity:         Pilled         Thread Style:         Dariel Quantity:         20         Head Style:         Stook Stangel         Stook Style:<!--</th--><th>Thread Class:</th><th></th></th>	3a         Thread Direction:         Right-hand         Thread Length:         0.875 inches         Fastener Length:         0.875 inches         Head Style:         Nead Style:         O.150 inches         Width Between Flats:         0.440 inches         Thread Diameter:         0.062 inches         Hole Quantity:         0.62         Thread Diameter:         0.250 inches         Hole Quantity:         Pilled         Thread Style:         Dariel Quantity:         20         Head Style:         Stook Stangel         Stook Style: </th <th>Thread Class:</th> <th></th>	Thread Class:	
Tread Direction: Right-hand Thread Length: 0.875 inches Fastener Length: 0.875 inches Head Style: Hexagon Head Height: 0.875 inches Head Height: 0.875 inches Head Height: 0.150 inches Width Between Flats: 0.150 inches Width Between Flats: 0.440 inches Hole Diameter: 0.440 inches Hole Diameter: 0.450 inches Hole Diameter: 0.450 inches Hole Quantity: 6 Hole Type: Drilled Thread Diameter: 0.250 inches Hole Type: Drilled Thread Yup Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material Specification: Sae asan standard single material response Surface Treatment: Cadmium Surface Treatment: Cadmium Surface Treatment Specification: Ans 2400 asan standard single treatment response Thread Series Designator: Unc Sheif Life:	Tread Direction:         Right-hand         Thread Length:         0.875 inches         Fastener Length:         0.875 inches         Head Style:         Otion Indes         Width Between Flats:         0.440 inches         Hole Diameter:         0.062 inches         Hole Quantity:         0.50 inches         Hole Quantity:         0.250 inches         Hole Quantity:         0.250 inches         Hole Quantity:         Dilled         Thread Style:         Dirled         Hole Configuration Style:         Store Configuration Style:         Hexagon Iongitudinal hole         Material Specification:         Store Cor Teatment:      <		
Right-hand   Thread Length:   0.875 inches   Fastener Length:   0.875 inches   Head Style:   Head Style:   Hexagon   Head Height:   0.150 inches   Width Between Flats:   0.440 inches   Hole Diameter:   0.420 inches   Hole Quantity:   0   Priled   Thread Diameter:   0.250 inches   Hole Quantity:   0   Priled   Thread Diameter:   0.350 inches   Hole Quantity:   0   Priled   Thread Diameter:   0.150 inches   Hole Quantity:   0   Priled   Thread Oty Per Inch (tpi):   20   Partice Thread Diameter:   0.0 rockwell c and 35.0 rockwell c   Hole Configuration Style:   Hexagon Iongitudinal hole   Material:   Steel comp 8640   Material Specification:   Steal Standard single material response   Surface Treatment:   Cadmium   Strafee Treatment Specification:   Ans 2400 assn standard single treatment response   Thread Series Designator:   Unc   Hord Series Designator:   Unc	Right-hand   Thread Length:   0.875 inches   Fastener Length:   0.875 inches   Head Style:   Head Style:   Head Style:   Head Meight:   0.150 inches   Width Between Flats:   0.440 inches   Hole Diameter:   0.062 inches   Hole Quantity:   0.50 inches   Hole Quantity:   0   0   101   Pread Quy Per Inch (tpi):   20   Hadenses Rating:   30.0 rockwell c and 35.0 rockwell c   Hoe Zonfiguration Style:   Hexagon longitudinal hole   Material:   Steel comp 8640   Material Specification:   Cadmium   Surface Treatment:   Cadmium   Startos Extended single material response   Cardmium   Surface Treatment:   Ling Steile Steiligation:   Cadmium   Surface Treatment:   Ling Steile Steiligation:   Cadmium   Surface Treatment Specification:   Autorial Specification:   Cadmium   Surface Treatment Specification:   Cadmium   Surface Treatment Specification:   Ling Steile Steiligation:   Cadmium   Surface Treatment Specification:   Ling Steile Steiligation:   Surface Treatment Specification:   Cadmium   Surface Treatment Specification:   Cadmium   Surface Treatment Speci		
Thread Length: 0.875 inches Fastener Length: 0.875 inches Fastener Length: 0.875 inches Head Style: Hexagon Head Height: 0.150 inches Head Height: 0.150 inches Width Between Flats: 0.440 inches Hole Diameter: 0.082 inches Thread Diameter: 0.082 inches Hole Quantity: 6 Hole Quantity: 6 Hole Quantity: 7 Head Quy Per Inch (tpi): 7 10 Hardness Rating: 7 10.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment Cadmium Line Surface Treatment Specification: Cadmium Line Surface Treatment response Cadmia Surface Treatment response Cadmia Surface Treatment response Cadmia Surface Treatment response Cadmia Surface Treatment Specification: Cadmia Surface Treatment response Cadmia Surface Treatment response Cadmia Surface Treatment Specification: Cadmia Surface Treatment response Cadmia Surface Treatment response Cadmia Surface Treatment Specification: Cadmia Surfa	Tread Length:         0.875 inches         Fastener Length:         0.875 inches         Head Style:         Head Style:         Hexagon         Head Height:         0.150 inches         Width Between Flats:         0.440 inches         Hole Diameter:         0.052 inches         Hole Quantity:         0.420 inches         Hole Quantity:         6         Hole Quantity:         7         Priled         Thread Valy Per Inch (tpi):         20         Hole Configuration Style:         Hexagon longitudinal hole         Material:         Stel comp 8640         Material:         Stafe Treatment:         Cadmium         Striface Treatment Specification:         Striface Treatment Specification:         Ans 2400 assn standard single treatment response         Thread Series Designator:         Unc         Sheff Life:         Na		
0.875 inches         Fastener Length:         0.875 inches         Head Style:         Hexagon         Head Height:         0.150 inches         Width Between Flats:         0.440 inches         Hole Diameter:         0.062 inches         Thread Diameter:         0.250 inches         Hole Quantity:         6         Hole Type:         Drilled         Thready Qty Per Inch (tpi):         20         Hardness Rating:         30.0 rockwell c and 35.0 rockwell c         Hole Configuration Style:         Hexagon longitudinal hole         Material:         Steel comp 8640         Material Specification:         Sae assn standard single material response         Surface Treatment:         Cadmium         Surface Treatment Specification:         Ama 2400 assn standard single treatment response         Thread Series Designator:         Unc         Shelf Life:	0.875 inches         Fastener Length:         0.875 inches         Head Style:         Hexagon         Head Height:         0.150 inches         Width Between Flats:         0.440 inches         Hole Diameter:         0.052 inches         Hole Quantity:         0         6         Hole Type:         Drilled         Thread Qty Per Inch (tpi):         20         Hardenses Rating:         30.0 rockwell c and 35.0 rockwell c         Hole Configuration Style:         Hexagon longitudinal hole         Material:         Steal comp 8640         Material:         Starface Treatment:         Cadmium         Surface Treatment Specification:         Ans 2400 assn standard single treatment response         Thread Series Designator:         Unc         Sheff Life:         Na	-	
Fastener Length:0.875 inchesHead Style:HexagonHead Height:0.150 inchesWidth Between Flats:0.440 inchesHole Diameter:0.062 inchesThread Diameter:0.052 inchesHole Quantity:06Hole Type:DrilledThready Qty Per Inch (tpi):20Hardness Rating:0.00 rockwell c and 35.0 rockwell cHole Configuration Style:Hexagon longitudinal holeMaterialSteel comp 8640Material Specification:Sa e assn standard single material responseSurface Treatment:CadmiumSurface Treatment Specification:Ans 2400 assn standard single treatment responseThread Specification:Ans 2400 assn standard single treatment responseSurface Treatment Specification:Anse 2400 assn standard single treatment responseSurface Treatment Specification: <td>Fastener Length:0.875 inchesHead Style:HexagonHead Height:0.150 inchesWidth Between Flats:0.440 inchesHole Diameter:0.062 inchesThread Diameter:0.052 inchesHole Quantity:07PrilledThready Qty Per Inch (tpi):20Hardness Rating:30.0 rockwell c and 35.0 rockwell cHole Configuration Style:Head and single material responseSurface Treatment:CadmiumSurface Treatment:CadmiumSurface Treatment:Curface Treatment:Curface</td> <td>-</td> <td></td>	Fastener Length:0.875 inchesHead Style:HexagonHead Height:0.150 inchesWidth Between Flats:0.440 inchesHole Diameter:0.062 inchesThread Diameter:0.052 inchesHole Quantity:07PrilledThready Qty Per Inch (tpi):20Hardness Rating:30.0 rockwell c and 35.0 rockwell cHole Configuration Style:Head and single material responseSurface Treatment:CadmiumSurface Treatment:CadmiumSurface Treatment:Curface	-	
0.875 inches Head Style: Hexagon Head Height: 0.150 inches Width Between Flats: 0.440 inches Hole Diameter: 0.062 inches Thread Diameter: 0.062 inches Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment Specification: Cardinum Surface Treatment Specification: Ans 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	0.875 inches Head Style: Hexagon Head Height: 0.150 inches Width Between Flats: 0.440 inches Hole Diameter: 0.440 inches Hole Diameter: 0.062 inches Thread Diameter: 0.250 inches Hole Quantity: 0.250 inches Hole Quantity: 0.250 inches Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: Na		
Head Style:HexagonHead Height:0.150 inchesWidth Between Flats:0.440 inchesHole Diameter:0.662 inchesThread Diameter:0.662 inchesHole Quantity:6Hole Type:DrilledThready Qty Per Inch (tpi):20Hole Configuration Style:Hole Configuration Style:Hexagon longitudinal holeMaterial:Steel comp 8640Material Specification:Sa assn standard single material responseSurface Treatment:CadmiumSurface Treatment Specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:Shelf Life:	Head Style:HexagonHead Height:0.150 inchesWidth Between Flats:0.440 inchesHole Diameter:0.062 inchesThread Diameter:0.250 inchesHole Quantity:6Hole Type:DrilledThready Qty Per Inch (tpi):20Hardness Rating:30.0 rockwell c and 35.0 rockwell cHole Configuration Style:Hexagon longitudinal holeMaterial:Steel comp 8640Material Specification:Sa assn standard single material responseSurface Treatment Specification:Ang 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:Na		
HexagonHead Height:0.150 inchesWith Between Flats:0.440 inchesHole Diameter:0.062 inchesThread Diameter:0.250 inchesHole Quantity:6Hole Type:DrilledThready Qty Per Inch (tpi):20Hardness Rating:30.0 rockwell c and 35.0 rockwell cHole Configuration Style:Hexagon longitudinal holeMaterialSteel comp 8640Material Specification:Sae assn standard single material responseSurface Treatment:CadmiumMateriad Specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:	HexagonHead Height:0.150 inchesWidth Between Flats:0.440 inchesHole Diameter:0.062 inchesThread Diameter:0.250 inchesHole Quantity:6Hole Type:DrilledThready Qty Per Inch (tpi):20Hole Configuration Style:Hosagon longitudinal holeMaterial:Steel comp 8640Material Specification:Sa assn standard single material responseSurface Treatment:CadmiumSurface Treatment specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:Na		
Head Height:0.150 inchesWidth Between Flats:0.440 inchesHole Diameter:0.062 inchesThread Diameter:0.250 inchesHole Quantity:6Hole Type:DrilledThready Qty Per Inch (tpi):20Hardness Rating:30.0 rockwell c and 35.0 rockwell cHole Configuration Style:Hexagon longitudinal holeMaterial:Steel comp 8640Material Specification:Sae assn standard single material responseSurface Treatment:CadmiumSurface Treatment Specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:	Head Height:0.150 inchesWidth Between Flats:0.440 inchesHole Diameter:0.062 inchesThread Diameter:0.250 inchesHole Quantity:6Hole Type:DrilledThready Qty Per Inch (tpi):20Hardness Rating:30.0 rockwell c and 35.0 rockwell cHole Configuration Style:Hexagon longitudinal holeMaterialSteel comp 8640Material Specification:Sae assn standard single material responseSurface Treatment Specification:CadmiumMaterial Specification:CadmiumSurface Treatment Specification:Ins 2400 assn standard single treatment responseThread Series Designator:UncSheff Life:Na		
<ul> <li>n.150 inches</li> <li>Width Between Flats:</li> <li>0.440 inches</li> <li>Hole Diameter:</li> <li>0.062 inches</li> <li>Thread Diameter:</li> <li>0.250 inches</li> <li>Hole Quantity:</li> <li>6</li> <li>Hole Quantity:</li> <li>6</li> <li>Hole Type:</li> <li>Drilled</li> <li>Thready Qty Per Inch (tpi):</li> <li>20</li> <li>Hardness Rating:</li> <li>30.0 rockwell c and 35.0 rockwell c</li> <li>Hole Configuration Style:</li> <li>Hexagon longitudinal hole</li> <li>Material:</li> <li>Steel comp 8640</li> <li>Material Specification:</li> <li>Sae assn standard single material response</li> <li>Surface Treatment Specification:</li> <li>Ams 2400 assn standard single treatment response</li> <li>Thread Series Designator:</li> <li>Unc</li> <li>Shelf Life:</li> </ul>	0.150 inches Width Between Flats: 0.440 inches Hole Diameter: 0.062 inches Thread Diameter: 0.250 inches Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: Na	-	
0.440 inches Hole Diameter: 0.062 inches Thread Diameter: 0.250 inches Hole Quantity: 0.250 inches Hole Quantity: 0 Hole Quantity: 0 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment Specification: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	0.440 inches Hole Diameter: 0.062 inches Thread Diameter: 0.250 inches Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment Specification: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	-	
Hole Diameter: 0.062 inches Thread Diameter: 0.250 inches Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Hole Diameter:         0.062 inches         Thread Diameter:         0.250 inches         Hole Quantity:         6         Hole Type:         Drilled         Thready Qty Per Inch (tpi):         20         Hardness Rating:         30.0 rockwell c and 35.0 rockwell c         Hole Configuration Style:         Hexagon longitudinal hole         Material:         Steel comp 8640         Material Specification:         Sae assn standard single material response         Surface Treatment:         Cadmium         Surface Treatment Specification:         Ams 2400 assn standard single treatment response         Thread Series Designator:         Unc         Shelf Life:         N/a	Width Between Flats:	
0.062 inches Thread Diameter: O.250 inches Hole Quantity: O Inches Hole Quantity: O Infled Hole Type: Drilled Thready Qty Per Inch (tpi): O Intready Qty Per Inch (tpi): D Intready Qty Per Inch (tpi): O Intready Qty Pe	0.062 inches Thread Diameter: O.250 inches Hole Quantity: 6 Hole Quantity: 7 O I O I O I O I O I O I O I O I O I O	0.440 inches	
Thread Diameter: 0.250 inches Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Thread Diameter: 0.250 inches Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	Hole Diameter:	
0.250 inches Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Hote Configuration Style: Steel comp 8640 Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	0.250 inches Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	0.062 inches	
Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	Thread Diameter:	
6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc	6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ans 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	0.250 inches	
Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc	Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Hole Quantity:	
Drilled Thready Qty Per Inch (tpi): 20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	DrilledThready Qty Per Inch (tpi):20Hardness Rating:30.0 rockwell c and 35.0 rockwell cHole Configuration Style:Hexagon longitudinal holeMaterial:Steel comp 8640Material Specification:Sae assn standard single material responseSurface Treatment:CadmiumSurface Treatment Specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:N/a	6	
Thready Qty Per Inch (tpi):20Hardness Rating:30.0 rockwell c and 35.0 rockwell cHole Configuration Style:Hexagon longitudinal holeMaterial:Steel comp 8640Material Specification:Sae assn standard single material responseSurface Treatment:CadmiumSurface Treatment Specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:	Thready Qty Per Inch (tpi):20Hardness Rating:30.0 rockwell c and 35.0 rockwell cHole Configuration Style:Hexagon longitudinal holeMaterial:Steel comp 8640Material Specification:Sae assn standard single material responseSurface Treatment:CadmiumSurface Treatment Specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:N/a	Hole Type:	
20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	20 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	Drilled	
Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Hardness Rating: 30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	Thready Qty Per Inch (tpi):	
30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	30.0 rockwell c and 35.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	20	
Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Hole Configuration Style:Hexagon longitudinal holeMaterial:Steel comp 8640Material Specification:Sae assn standard single material responseSurface Treatment:CadmiumSurface Treatment Specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:N/a	Hardness Rating:	
Hexagon longitudinal hole   Material:   Steel comp 8640   Material Specification:   Sae assn standard single material response   Surface Treatment:   Cadmium   Surface Treatment Specification:   Ams 2400 assn standard single treatment response   Thread Series Designator:   Unc   Shelf Life:	Hexagon longitudinal hole Material: Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	30.0 rockwell c and 35.0 rockwell c	
Material:Steel comp 8640Material Specification:Sae assn standard single material responseSurface Treatment:CadmiumSurface Treatment Specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:	Material:Steel comp 8640Material Specification:Sae assn standard single material responseSurface Treatment:CadmiumSurface Treatment Specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:N/a	Hole Configuration Style:	
Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Steel comp 8640 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	Hexagon longitudinal hole	
Material Specification:Sae assn standard single material responseSurface Treatment:CadmiumSurface Treatment Specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:	Material Specification:Sae assn standard single material responseSurface Treatment:CadmiumSurface Treatment Specification:Ams 2400 assn standard single treatment responseThread Series Designator:UncShelf Life:N/a	Material:	
Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Sae assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	Steel comp 8640	
Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Surface Treatment: Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	Material Specification:	
Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Cadmium Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	Sae assn standard single material response	
Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Surface Treatment Specification: Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a	Surface Treatment:	
Ams 2400 assn standard single treatment response Thread Series Designator: Unc Shelf Life:	Ams 2400 assn standard single treatment response <b>Thread Series Designator:</b> Unc <b>Shelf Life:</b> N/a	Cadmium	
Thread Series Designator: Unc Shelf Life:	Thread Series Designator: Unc Shelf Life: N/a	Surface Treatment Specification:	
Unc Shelf Life:	Unc Shelf Life: N/a	Ams 2400 assn standard single treatment response	
Shelf Life:	Shelf Life: N/a	Thread Series Designator:	
	N/a	Unc	
N/a		Shelf Life:	
	Unit Of Measure:	N/a	

---

## NSN 5305-00-639-7334

Hexagon Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

