

View Online at <https://aerobasegroup.com/nsn/5305-00-649-8587>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.345 inches and 0.438 inches

**Fastener Length:**

3.075 inches

**Head Style:**

Fillister countersunk

**Head Diameter:**

Between 0.235 inches and 0.245 inches

**Head Height:**

Between 0.132 inches and 0.156 inches

**First Diameter From Head:**

Between 0.116 inches and 0.119 inches

**Second Diameter From Head:**

Between 0.139 inches and 0.145 inches

**Third Diameter From Head:**

Between 0.224 inches and 0.244 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.325 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

2.575 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

2.637 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

90.0 degrees

**Externally Relieved Body Diameter Quantity:**

1

**Product Name:**

Navy special project

**Special Features:**

Furnished w/captive washer on thd end

**Material:**

Steel

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

580-0025-00 fscm 90107 mfr ref single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0