NSN 5305-00-649-9011

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-649-9011 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.364 inches **Fastener Length:** 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.427 inches and 0.447 inches **Head Height:** 0.125 inches **First Diameter From Head:** Between 0.285 inches and 0.291 inches **Second Diameter From Head:** Between 0.301 inches and 0.306 inches **Third Diameter From Head:** 0.129 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.031 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.101 inches and 0.109 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.125 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Special Features:** 63 microinch finish Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response

Surface Treatment:

Passivate

NSN 5305-00-649-9011

Externally Relieved Body Screw - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0