

View Online at <https://aerobasegroup.com/nsn/5305-00-649-9011>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.364 inches

**Fastener Length:**

0.625 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.427 inches and 0.447 inches

**Head Height:**

0.125 inches

**First Diameter From Head:**

Between 0.285 inches and 0.291 inches

**Second Diameter From Head:**

Between 0.301 inches and 0.306 inches

**Third Diameter From Head:**

0.129 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.031 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.101 inches and 0.109 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

0.125 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

63 microinch finish

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0