Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-649-9011

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.364 inches
Fastener Length:
0.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.427 inches and 0.447 inches
Head Height:
0.125 inches
First Diameter From Head:
Between 0.285 inches and 0.291 inches
Second Diameter From Head:
Between 0.301 inches and 0.306 inches
Third Diameter From Head:
0.129 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.031 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Between 0.101 inches and 0.109 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
0.125 inches
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
24
Externally Relieved Body Diameter Quantity:
1
Special Features:
63 microinch finish
Material:
Steel comp 303
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Special Features: 63 microinch finish
Material:
-
Passivate

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0