NSN 5305-00-652-4562

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-652-4562

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.215 inches and 0.220 inches
Fastener Length:
0.300 inches
Head Style:
Fillister
Head Diameter:
Between 0.292 inches and 0.313 inches
Head Height:
Between 0.165 inches and 0.180 inches
Shoulder Diameter:
0.2175 inches first shoulder and 0.2180 inches first shoulder
Shoulder Length:
0.080 inches first shoulder and 0.085 inches first shoulder
Hole Diameter:
0.047 inches
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hole Configuration Style:
Round
Shoulder Shape:
Round first shoulder
Material:
Steel comp 4140
Surface Treatment:
Cadmium
Surface Treatment Specification:

ourrace rreatment opecations

Qq-p-416 ty1 cl3 federal specification single treatment response

NSN 5305-00-652-4562

Shoulder Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A003b0