## NSN 5305-00-652-5678

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-652-5678

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.313 inches and 0.437 inches
Fastener Length:
0.800 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.182 inches and 0.189 inches
Head Height:
Between 0.097 inches and 0.103 inches
Shoulder Diameter:
0.185 inches first shoulder and 0.187 inches first shoulder
Shoulder Length:
0.050 inches first shoulder
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Shoulder Shape:
Round first shoulder
Special Features:
Undercut 0.050 in. Lg, 0.147 in. Min 0.149 in. Maximum lg
Material:
Steel comp 1213
Surface Treatment:
Phosphate
Surface Treatment Specification:
Mil-f-14072 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5305-00-652-5678

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.