## NSN 5305-00-652-7000

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-652-7000 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.313 inches **Fastener Length:** Between 0.375 inches and 0.405 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.100 inches and 0.110 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Primary Washer Outside Diameter:** Between 0.372 inches and 0.383 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** Between 0.020 inches and 0.025 inches **Special Features:** Point diameter 0.124 in. Min 0.138 in. Max Material: Copper alloy 172 **Material Specification:** Ams 2800 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Unit Of Measure:
-Demilitarization:

## NSN 5305-00-652-7000

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0