## NSN 5305-00-655-6406

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-655-6406
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.203 inches and 0.235 inches
Fastener Length:
Between 0.614 inches and 0.666 inches
Head Style:
Pan
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.105 inches and 0.115 inches
First Diameter From Head:
Between 0.104 inches and 0.114 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.411 inches and 0.431 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 303
Material Specification:
Mil-s-7720 military specification single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A003b0

## NSN 5305-00-655-6406

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-7720 spec.