NSN 5305-00-655-6556

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-655-6556

Thread Direction: Right-hand Thread Length: Between 1.688 inches and 1.750 inches Fastener Length: 1.750 inches Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material: Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	
Thread Direction: Right-hand Thread Length: Between 1.688 inches and 1.750 inches Fastener Length: 1.750 inches Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	Thread Class:
Right-hand Thread Length: Between 1.688 inches and 1.750 inches Fastener Length: 1.750 inches Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	2a
Thread Length: Between 1.688 inches and 1.750 inches Fastener Length: 1.750 inches Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	
Between 1.688 inches and 1.750 inches Fastener Length: 1.750 inches Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	·
Fastener Length: 1.750 inches Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	Thread Length:
1.750 inches Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	Between 1.688 inches and 1.750 inches
Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	Fastener Length:
Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	1.750 inches
Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	Head Style:
Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	Fillister
Head Height: Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	Head Diameter:
Between 0.123 inches and 0.130 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	Between 0.292 inches and 0.313 inches
Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification all treatment responses Head Hole Configuration Style: Round	Head Height:
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	Between 0.123 inches and 0.130 inches
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	Hole Diameter:
Cross recess type 1 Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	0.046 inches
Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	Internal Drive Style:
O.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	Cross recess type 1
Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	Thread Diameter:
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	0.190 inches
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	Hole Quantity:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	1
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	The set of Bestell (C)
55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	Inready Qty Per Inch (tpi):
Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	
Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	32
Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	32 Min. Tensile Strength (psi):
Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	32 Min. Tensile Strength (psi): 55000 pounds per square inch
Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material:
Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel
Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round	Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response
Head Hole Configuration Style: Round	Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment:
Round	Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate
	Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification:
Thread Series Designator:	Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses
Timeda Corico Decignator:	Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style:
Unf	Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style:
Shelf Life:	Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round Thread Series Designator:
N/a	Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round Thread Series Designator: Unf
	Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round Thread Series Designator: Unf Shelf Life:
	Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses Head Hole Configuration Style: Round Thread Series Designator: Unf Shelf Life:

--

NSN 5305-00-655-6556

Machine Screw - Page 2 of 2



em			

No

Fiig:

A500d0