Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-655-6616

-	
	d Class:
2a	
	d Direction:
Right-h	
	d Length:
	en 0.340 inches and 0.400 inches
Faster	ner Length:
1.070 i	inches
Head S	Style:
Knurle	d no. 1
Head I	Diameter:
Betwee	en 0.750 inches and 0.810 inches
Head I	Height:
0.370 i	inches
First D	Diameter From Head:
0.185 i	nches
Distan	ce From Largest Bearing Surface Of Head To End Of First Diameter:
0.700 i	inches
Interna	al Drive Style:
Slot	
Thread	d Diameter:
0.250 i	inches
Thread	dy Qty Per Inch (tpi):
20	
Extern	ally Relieved Body Diameter Quantity:
1	
Materi	al:
Steel c	comp 303
Materi	al Specification:
Mil-s-7	720 military specification single material response
Surfac	e Treatment:
Passiv	ate
Surfac	e Treatment Specification:
Mil-s-5	002 military specification single treatment response
Thread	d Series Designator:
Unc	
Shelf I	Life:
N/a	
Unit O	f Measure:
Demili	tarization:
No	

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-s-7720 spec.