NSN 5305-00-655-7577



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-655-7577 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.443 inches and 0.510 inches **Fastener Length:** Between 0.953 inches and 1.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Hole Diameter:** 0.076 inches **Grip Diameter:** Between 0.2483 inches and 0.2492 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.490 inches and 0.510 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Hole Configuration Style:** Hexagon perpendicular **Countersink Angle:** 100.0 degrees Material: Steel **Thread Series Designator:** Unjf

Specification Data:

80205-nas334c+7-5 professional/industrial association standard

NSN 5305-00-655-7577

Close Tolerance Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0