## NSN 5305-00-656-0051

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-656-0051 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.355 inches **Fastener Length:** 0.438 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.359 inches and 0.385 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** 100.0 degrees Material: Steel comp 4037 or steel comp 8630 **Material Specification:** Ams-6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf **Departure From Cited Designator:** As mod by locking feature Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-00-656-0051

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.