## NSN 5305-00-656-7210

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-656-7210

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.443 inches and 0.510 inches
Fastener Length:
Between 2.391 inches and 2.438 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.497 inches and 0.507 inches
Grip Diameter:
Between 0.2487 inches and 0.2492 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Grip Length:
Between 1.928 inches and 1.948 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches grip
Product Name:
Navy special project
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response
Thread Series Designator:
Unf
Specification Data:
80205-nas334 professional/industrial association standard

N/a

Shelf Life:

## NSN 5305-00-656-7210

Close Tolerance Screw - Page 2 of 2



U	nit	Of	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.