## NSN 5305-00-660-1939

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-660-1939 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.294 inches and 0.344 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Fillister **Head Diameter:** Between 0.138 inches and 0.168 inches **Head Height:** Between 0.069 inches and 0.079 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel **Screw Material Specification:** Qq-s-634 federal specification single material response or qq-s-637 federal specification single material response or 66 federal standard single material response **Screw Surface Treatment:** Phosphate zinc **Screw Surface Treatment Specification:** Mil-p-16232, type 2, cl 1 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 1 type and 4s style Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

A500d0

**Demilitarization:** 

## NSN 5305-00-660-1939

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-p-16232 spec.