NSN 5305-00-660-2310

Demilitarization:

No

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-660-2310 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.587 inches and 0.670 inches **Fastener Length:** 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.118 inches and 0.130 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.283 inches and 0.297 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.040 inches **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

NSN 5305-00-660-2310

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0