## NSN 5305-00-660-2416

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-660-2416 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.260 inches and 0.310 inches **Fastener Length:** Between 0.279 inches and 0.310 inches **Head Style:** Hexagon **Head Height:** Between 0.049 inches and 0.060 inches Width Between Flats: Between 0.181 inches and 0.187 inches **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Stainless steel **Screw Material Specification:** 66 federal standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Special Features:** Undercut 0.03 in. Width by 0.005 in. Deep **Thread Series Designator:** Unc **Specification Or Standard:** 2 type and 10p style **Departure From Cited Designator:** As modified by fastener length and special features Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## **NSN 5305-00-660-2416**Machine Screw - Page 2 of 2



Fiig:

A500d0